



ADHVEYA
DRYMIX INDIA PVT LTD

Strength engineered. Excellence delivered.

ACRYLIC SEALER

PREMIUM ACRYLIC SEALER FOR CONCRETE PROTECTION

Adhveya Acrylic Sealer is a high performance, premium quality acrylic based sealer designed to protect and enhance concrete surfaces. It penetrates deeply to form a clear protective barrier that reduces water absorption, resists dusting, and improves surface durability while maintaining the natural appearance.



**EXCELLENT
WATER REPELLENCY**



**UV & WEATHER
RESISTANT**



**PENETRATING
PROTECTION**



**ENHANCES SURFACE
APPEARANCE**



**REDUCES DUSTING
& POWDERING**



**RESISTANT TO
ALKALI**



EASY TO APPLY



**LONG LASTING
PROTECTION**



**LOW ODOUR
& NON-YELLOWING**



**INTERIOR &
EXTERIOR USE**



**EXCELLENT WATER REPELLENCY
PROTECTS AGAINST MOISTURE INGRESS**



**PENETRATING & BREATHABLE
ALLOWS SURFACE TO BREATHE**



**ENHANCES DURABILITY
EXTENDS SURFACE LIFE**



**LOW ODOUR & NON-YELLOWING
CLEAR FINISH, LONG LASTING**



**PACKAGING
5 L CAN**



**CONCRETE PROTECTION
& SEALING**



**FLOORS, WALLS
& FACADES**



**DRIVEWAYS, PATHWAYS
& PARKING AREAS**



**RESIDENTIAL, COMMERCIAL
& INDUSTRIAL USE**

ACRYLIC SEALER

PREMIUM ACRYLIC SEALER FOR CONCRETE PROTECTION

HIGH PERFORMANCE ACRYLIC SEALING SOLUTION



PRODUCT DESCRIPTION

Adhveya Acrylic Sealer is a high performance, premium quality acrylic based sealer designed to protect and enhance concrete surfaces. It penetrates deeply to form a clear protective barrier that reduces water absorption, resists dusting, and improves surface durability while maintaining the natural appearance.



RECOMMENDED USES



CONCRETE
FLOORS



WALLS &
FACADES



WAREHOUSES &
FACILITIES



PARKING
STRUCTURES



DRIVEWAYS &
PATHWAYS



COMMERCIAL &
INDUSTRIAL
BUILDINGS



TECHNICAL PROPERTIES (TYPICAL VALUES)

PROPERTY	TYPICAL VALUES
Appearance	Clear, colorless liquid
Base	Acrylic Polymer Solution
Specific Gravity	1.00 ± 0.05
pH	8.0 – 9.0
Solids Content	18 – 22%
VOC Content	Low VOC (Solvent Free)
Coverage	Approx. 6 – 8 m ² / L (Depending on surface porosity)
Drying Time	1 – 2 hours
Recoating Time	2 – 4 hours
Full Cure	7 days
Shelf Life	12 months in unopened pack

* The above values are typical and may vary based on site conditions.



SURFACE PREPARATION

The concrete surface must be structurally sound and free from loose or unsound concrete, oil, grease, paint, curing compounds, dust, laitance and other contaminants. Prepare the surface by mechanical means such as grinding, shot blasting or diamond grinding to obtain a clean, open and porous texture. Remove all debris and dust using industrial vacuum cleaning.



PRECAUTIONS

- Do not apply below 5°C or above 35°C.
- Do not apply in direct sunlight.
- Do not add any water, thinner or solvent.
- Do not re-temper or dilute.
- Use within the pot life.
- For professional use only.



PACKAGING

Available in
5 L Can



ADVANTAGES

- ✓ Excellent water repellency
- ✓ Penetrating protection
- ✓ Reduces dusting & powdering
- ✓ Enhances surface appearance
- ✓ Long lasting protection
- ✓ UV & weather resistant
- ✓ Easy to apply
- ✓ Low odour & non-yellowing
- ✓ Interior & exterior use
- ✓ Environment friendly



MIXING

Acrylic Sealer is ready to use. Do not dilute or mix with water, thinner or any other material.



READY
TO USE



APPLY BY
ROLLER / SPRAYER
OR LOW PRESSURE



KEEP SURFACE
WET FOR
20-30 MINUTES



REMOVE EXCESS
MATERIAL



ALLOW TO DRY
NATURALLY



APPLICATION METHOD



1. SURFACE PREP

Ensure the surface is clean, sound and free from dust, oil, grease, laitance or loose particles.



2. APPLY

Apply Acrylic Sealer evenly by roller, brush or low pressure sprayer to achieve uniform coverage.



3. KEEP WET

Keep the surface wet for 20-30 minutes for better penetration.



4. REMOVE EXCESS

Remove excess material from the surface before it dries using a mop or squeegee.



5. DRY & CURE

Allow the surface to dry naturally. Protect from water for at least 24 hours.



CURING

Proper curing is essential to achieve optimum performance. After application, protect the surface from rapid water loss and allow adequate curing. Keep the surface continuously moist / sheltered for a minimum of 3 days in hot or windy conditions, take additional measures to prevent premature drying.



STORAGE & SHELF LIFE

Shelf Life:
12 months from the date of manufacture in unopened original packing.

Storage:
Store in a cool, dry place away from direct sunlight and moisture.



HEALTH & SAFETY

Wear protective gloves, goggles and suitable clothing during application. Avoid contact with skin and eyes. In case of contact, flush with plenty of clean water and seek medical advice if irritation persists.



MANUFACTURED BY:

ADHVEYA DRYMIX INDIA PVT LTD

KUBER INDUSTRIAL PARK
VALSAD, GUJARAT, INDIA



adhveya@gmail.com



www.adhveya.com | www.adhveya.in